



A BRIGHTER FUTURE

UK **LED** *lighting*

Artaris 800 LED Ceiling Light

V0 Fire rated

LDT files




IP40

High CRI option

Dimmable



Part No.	ARTAR800-30-60W-80-FL-W-O-DI-SM-DA
LED	CREE
CCT	2700K / 3000k / 4000K / 5700K
Lumens 60W	6600
Lumens 80W	8800
Beam Angle	120 °
Power Consumption	60W to 80W Adjustable Driver
Volt/DC	220
Driver	Osram Flicker free Driver
Dimming	Dali or Triac Dimming
Dimensions	800 x 86
PC diffuser	94-V0 fire rated
Lumen /Watt	110 (3000K)
Life expectancy	50,000 Hours L70




Artaris Flat




Artaris Curved



Artaris Opal or Micro Prismatic Diffuser




Opal cover



Microprismatic diffuser



Artaris Flat & Curved Wall Installation




Artaris Flat Direct and Indirect Lighting

Artaris Curved Direct and Indirect Lighting



Artaris Flat Direct and Indirect Wall Lighting



Artaris Flat & Curved Pendant Suspension Cables



Artaris Flat & Curved Pendant Pole Mounted



Part numbering key

CCT : 2700K -5700K

60W to 80W

FL : Flat
CR : Curved

O : Opal Diffuser
M : Micro Prismatic Diffuser

DA : Dali Dimming
TR : Triac Dimming
SW : Switched Driver

Artaris Ceiling Light

ARTAR800-30-60W-80-FL-W-O-DI-SM-DA

80 :CRI 80
90 :CRI 90

W: White
B : Black

D: Direct Light only
DI : Direct & Indirect

SM : Surface Mounted
SU : Suspended (Suspension Cables)
PM : Suspended Pole Mounted